

V-Force Wiring Pin Outs

Part # 67037

LAND ROVER / RANGE ROVER

<u>Year</u>	<u>Model</u>	<u>Engine</u>	<u>TPS Wire Color</u>	<u>TPS Location</u>	<u>MAP/ MAF Wire Color</u>	<u>MAP/ MAF Location</u>	<u>Footnotes</u>
2000-2002	DISCOVERY	4.0L	YEL/GRN	1	BLU/GRN	B	(**)
2003-2004	DISCOVERY	4.6L	YEL/GRN	1	BLU/GRN	B	(**)
2008-2009	LR2 HSE, SE	3.2L	BROWN	1	BLU/GRN	A	
2005-2009	LR3 HSE, SE	4.4L	RED	1	BLK/PRPL	A	
2006-2009	Range Rover HSE	4.2L	RED	1	BLK/PRPL	C	
2009	Range Rover HSE	4.4L	RED	1	BLK/PRPL	C	

02 Sensor Signal connections (all vehicles)

<u>Vehicle/Connector type</u>	<u>Wire Color</u>
Acura/Honda 4 Wire Connector	Black
Alfa Romeo 3 Wires	Black
Audi 3 Wires	Black
BMW 3 Wires	Black
BMW 4 Wires	Black
Chrysler 3 Wires	Black
Chrysler 4 Wires	Black
Chrysler Import 4 Wires	Black,Blue or Yellow
Ford 3 Wires	Black
Ford 4 Wires	Black
Geo 4 Wires	Black
GM 2 Wires	Black
GM 3 Wires	Black orPurple
GM 4 Wires	Black orPurple
Isuzu 3 Wires	Blue

Isuzu 4 Wires	Blue
Kia 3 Wires	Black
Lancia 3 Wires	Black
Land Rover	Black
Mazda 3 Wires	Black
Mazda 4 Wires	Black
Mercury 3 Wires	Black
Mercury 4 Wires	Black
Mitsubishi 4 Wires	Black,Blue or Yellow
Nissan 3 Wires	Black
Nissan 4 Wires	Black
Subaru 3 Wires	Black
Suzuki 4 wires	Black
Volkswagon	White

7/21/2010

Footnotes

(**) = Indicates that you will be connecting to the (MAF) Mass air flow sensor, all others connect to the (MAP) Manifold Absolute Press Sensor

TPS Locations

1 = The (TPS) Throttle position sensor is located on the throttle body

MAF/MAP Sensor Locations

A = Left front side of engine

B = In air intake assembly

C= Top rear of Engine